

### ELITE E-HYD-SB-15 (6/12) (hydraulic pipe spreader bar)

#### Equipped with:

##### Twin telescope arms

Hydraulic cylinders and piping onboard  
Hydraulic power pack with tank  
Electrically powered

- SWL of 15000kg
- 6m up to 12m pipe lengths

#### Applications:

- Indoor/ outdoor crane



- SWL: 15000kg
- 2 x rubber pipe bevel protection plates at pipe pin entry point
- 2 x rubber pipe inner lining protection plates on pipe pins
- 2 x Copper brass pipe bevel protection plates at possible pipe bevel contact points
- 2 x LED green flash lights indicating "Safe to lift".
- 1 x Siren with sensor indicating "telescopes are opening".
- Meter interval pipe length markings along outer side of telescopes 6m up to 12.9m
- Outer telescope pin locks for exact pipe length setup
- 2 x hydraulic cylinders for open/ retracting inner telescopes (1250mm stroke)

- Each hyd. Cylinder with 6000kg locking power
- Onboard hydraulic system and tank
- Oil spillage pan (bath) for total oil reservoir capacity
- Oil pressure gauge
- Oil flow values
- Synchronized cylinder movement

**Length:** 14525mm (Fully extended)

6530mm (Fully retracted)

**Width:** 600mm (Operational width)

**Height:** 2900mm (without tackle)

**Net weight:** 4950kg