

### Hydraulic power rotators & Yoke options

#### Rotators with:

**SWL of 12000kg, 18000kg and 22000kg including installed oscillation brake**

- Steel body and head rotator housing.
- Two ports for hydraulic oil entry/ exit
- Torque: 4000Nm
- Oil pressure: 320bar
- Oil flow: Minimum=15l/min. Optimal=25l/min
- 360° endless rotation
- Oscillation Pendle braking system
- Precise and perfectly control action
- Net weight: 12000kg model = 88kg  
18000kg model = 135kg  
22000kg model = 151kg (Torque 4800Nm)



#### Yokes with:

**SWL of 12000kg & 18000kg to suit both rotators**

#### Standard dedicated yoke:

**is manufactured to fit as per customers pin ID and excavator stick width.**

- Not adjustable.
- Pin included



#### Universal Multi yoke:

**engineered and created solely by Schoenbeck is an adjustable and flexible option that will accommodate 99% of all Crawler/ wheeled excavators manufactured worldwide.**

Formerly supplied to dealers only, this accessory is perfect when considering rental business or frequently substituted excavator brands during your project.

Supplied with adjustable slide arms, numerous pin sizes from OD60mm up to 110mm, bushes and spacers.

**Call or email us for further information or the contact details of your local agent or distributor.**